

# IV-Stand Low Gravity

## 8 Hooks

### I-LOW015

#### PRODUCT DESCRIPTION

|                                      |   |
|--------------------------------------|---|
| <b>Field of application</b>          | Intensive Care                          |
| <b>Material</b>                      | Stainless steel/ Plastic                |
| <b>Colour of plastic parts</b>       | Blue / Black                            |
| <b>Number of hooks</b>               | 8                                       |
| <b>Arrangement of the hooks</b>      | 90° to each other                       |
| <b>Type of height adjustment</b>     | Stainless steel screw height adjustment |
| <b>Maximum length/height</b>         | 2.270 mm                                |
| <b>Minimum length/height</b>         | 1.420 mm                                |
| <b>Inner tube diameter</b>           | Ø 25 mm                                 |
| <b>Outer tube diameter</b>           | Ø 33,7 mm                               |
| <b>Length of outer tube</b>          | 1.200 mm                                |
| <b>Base leg profile</b>              | Ø 33,7 mm                               |
| <b>Base weight</b>                   | Weighted                                |
| <b>Base diameter</b>                 | Ø 680 mm                                |
| <b>Castors</b>                       | Apparatus castors                       |
| <b>Castor diameter</b>               | Ø 75 mm                                 |
| <b>Number of castors</b>             | 5 with brakes and elect. conductivity   |
| <b>Total load capacity (kg)</b>      | 13                                      |
| <b>Load capacity per system (kg)</b> | 8                                       |
| <b>Load capacity per hook (kg)</b>   | 2                                       |



#### PACKAGING UNIT: UNIT

|             |          |
|-------------|----------|
| Width Box1  | 0,21 m   |
| Height Box1 | 0,13 m   |
| Length Box1 | 1,46 m   |
| Weight Box1 | 12,50 kg |



## IV-Stand Low Gravity



### Area of application

The outer tube offers enough space to attach various devices at a user-friendly operating height



### Technology

- All plastic parts are lightweight
- Stainless steel tubes according to DIN EN 10217-7
- Material ultrasonic and eddy current tested (according to EN 10246-9/3)
- The integrated pull-out limiter prevents the adjustable tubes from separating
- Safety bottle cross according to DIN ISO 15375
- Increased resistance to corrosion thanks to the base made of glass-fibre reinforced plastic



### Economy

Compact packaging allows for low-cost shipping



### Safety

- The base legs are sealed with plastic plugs (no risk of injury)
- Low risk of pinching when retracting and extending the IV-pole thanks to the built-in safety distance
- The Softdrop system dampens and controls the lowering of the inner tube
- No risk of injury thanks to the rounded shape of the bottle hooks
- The geometry of the hooks prevents the infusion bottle from falling out

